

MILLENIUM METREX™

METEL SERIES

PRODUCT FEATURES:

- » Surface wall mount
- » Self contained emergency light
- » Self diagnostic testing features
- » High impact polycarbonate construction



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

SHIELD: UV-stabilized, high impact, injection molded clear polycarbonate. Nominal thickness .120". Captive stainless steel Torx® T-20 with center pin fasteners secure shield to housing. Continuous closed cell silicone gasket seals shield to housing.

HOUSING: High impact, injection molded polycarbonate. Housing provided with four-point mounting holes, one wireway hole and temporary junction box mounting drill points – see Cross Section/Details. Closed cell die-cut Neoprene gasket seals housing to mounting surface.

ELECTRICAL: Electrical components mounted to removable chassis. Sealed nickel-cadmium Emergency Battery Pack with standard deep cycle battery conditioning, self test and self diagnostic circuitry, remote laser activated test switch, protected mechanical test switch and status indicator. Suitable for 10°C to 45°C (50°F to 113°F). Cold Weather Emergency Battery Pack (CL) suitable for -30°C to 45°C (-22°F to 113°F). Remote Exit Ready – can power one or two Kenall METSS Satellite Exits. Can also power Kenall METER Emergency Remote Unit(s); selected total lamps – including all remotes – cannot exceed unit output rating; consult Output Rating chart.

INSTALLATION: Standard four-point mounting required for *Peace of Mind Guarantee*®. Drill points provided for optional surface conduit entry.

LISTINGS: UL and CUL listed for Wet Location. UL certified IP64 per IEC 60598. Meets or exceeds UL924 and NFPA 101 standards. Meets or exceeds CSA and NRCAN requirements.





ORDERING INFORMATION (Ex: METEL-24N-MW-2-6.5L-120)

Model	Battery Capacity	Finish	Lamp Qty	Lamp Wattage/Type	Voltage	Options	Accessories
METEL				6.5L			
Battery Capacity		Finish		Voltage		Accessories	
24N	24W Nickel Cadmium	MB	Matte Black	120	120 Volts	LP	Laser Pointer
40N	40W Nickel Cadmium	MW	Matte White	DT	120/277 Volts		
				DTC	120/347 Volts		
Lamp Quantity			Options				
2	2 Internal Lamps		CEL** Cold Weather Emergency Battery Pack				* Selected total lamps cannot exceed unit output rating. Consult Output Rating Chart on left **n/a with 40N battery capacity or DTC voltage
4	4 Internal Lamps (fixed optics)		PH Phillips Head Fasteners				
Lamp Wattage/Type*							
6.5L	6.5W LED						


Maximum Lamp Quantity	Battery ½ hr		1 hr		1½ hr		2 hr		3 hr		4 hr	
24N	5	5	3	2	--	--	--	--	--	--	--	--
40N	5	5	5	4	3	2	--	--	--	--	--	--

Remote distances based on wire gauge

DIMENSIONAL DATA



Baseplate Mounting View



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2022 Kenall Mfg. Co.