

# MILLENIUM METREX™

## METSU SERIES

### PRODUCT FEATURES:

- » Surface mount end – wall or ceiling; Single Face
- » Indirect Red or Green LED
- » Internal Battery Backup System
- » High impact polycarbonate construction



### PROJECT INFORMATION

Job Name \_\_\_\_\_

Fixture Type \_\_\_\_\_

Catalog Number \_\_\_\_\_

Approved by \_\_\_\_\_

### SPECIFICATIONS

**HOUSING:** High impact, injection molded polycarbonate. Housing provided with canopy mounting and wireway drill points top and side – see Cross Section/Details. Closed cell die-cut Neoprene gasket seals housing to canopy.

**SHIELD:** UV-stabilized, high impact, injection molded clear polycarbonate. Nominal thickness .120". Captive stainless steel Torx® T-20 with center pin fasteners secure shield to housing. Continuous closed cell silicone gasket seals shield to housing.

**CANOPY:** High impact, injection molded polycarbonate canopy cover with heavy gauge galvanized steel mounting plate with integral 1/4-20 threaded studs. Canopy mounting plate provided with four-point mounting holes, one wireway hole and temporary junction box mounting holes. Closed cell die-cut Neoprene gasket seals canopy to mounting surface.

**LEGEND:** Illuminated by internal high output LEDs. Lettering six inches high with .750" stroke. Polycarbonate red or green filter panels. High impact, injection molded polycarbonate stencil and field selectable chevron inserts.

**ELECTRICAL:** 624 nm Red or 527 nm Green LED light source. Electrical components mounted to removable high impact, injection molded polycarbonate chassis. Remote Exit Ready – can power one Kenall METSS Satellite Exit.

**OPTIONS:** Sealed nickel-cadmium Emergency Battery Pack (EL) with standard deep cycle battery conditioning, self test and self diagnostic circuitry, remote laser activated test switch, protected mechanical test switch and status indicator. Provides 120 minutes of emergency operation. The Emergency Battery Pack (EL) is suitable for 10°C to 45°C (50°F to 113°F). Cold Weather Emergency Battery Pack (CL) suitable for -30°C to 45°C (-22°F to 113°F). Remote Exit Ready – can power one or two Kenall METSS Satellite Exits.

**INSTALLATION:** Standard four-point mounting required for [Peace of Mind Guarantee®](#). Drill points provided for optional conduit entry.


**LISTINGS:** UL and CUL listed for Wet Location. UL certified IP64 per IEC 60598. Meets or exceeds UL924 and NFPA 101 standards. Meets or exceeds CSA and NRCAN requirements. NSF2 Splash/ Non-Food Zone.



### ORDERING INFORMATION (Ex: METSU-MW-R-DT-EL)

Model	Finish	Legend Color	Voltage	Options	Accessories
<b>METSU</b>					
	<b>Finish</b>		<b>Voltage</b>		<b>Accessories</b>
	<b>MB</b> Matte Black		<b>DT</b> 120/277 Volts		<b>LP</b> Laser Pointer
	<b>MW</b> Matte White		<b>DTC</b> 120/347 Volts		
	<b>Legend Color</b>		<b>Options</b>		
	<b>R</b> Red		<b>CEL</b> Cold Weather Emergency Battery Pack		
	<b>G</b> Green		<b>EL</b> Standard Emergency Battery Pack		
			<b>XAC</b> Auxiliary AC Supply (matches voltage selection)		
			<b>XDC</b> Auxiliary DC Supply (6-24 volts)		

### DIMENSIONAL DATA



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at [www.kenall.com/patents](http://www.kenall.com/patents). Content of specification sheets is subject to change; please consult [www.kenall.com](http://www.kenall.com) for current product details. ©2022 Kenall Mfg. Co.