

**SE**CLEANROOM &  
CONTAINMENT

# Moving beyond the MRI Suite: New Non-Ferrous Luminaire Options for Clean Spaces



## SimpleSeal NFCSEDI & NFCSESI Series

- Delivered lumen range: 4,160 – 15,535 lm
- Input power: 48 – 121W
- Efficacy: 86 – 129 lm/W
- Non-ferrous construction and remote power supplies provide safe operation with EMI-sensitive equipment
- Symmetric, optical distribution with uniform lens appearance
- Radiated and conducted emissions controlled as per MIL-STD-461G

Nominal size: 2' x 2'; 2' x 4'  
 Installation type: surface or recessed mount  
 Lamp type: LED

The new **SimpleSeal NFCSEDI & NFCSESI** luminaire families combine the best in non-ferrous construction and sealed performance to illuminate spaces where magnetically sensitive processes are performed. Kenall's years of expertise in lighting challenging environments means your application will be safely and completely sealed from both sides — the room and the plenum. And work spaces will be comfortably lit without the debilitating glare commonly associated with lower-quality, flat-panel lighting.

**KENALL**

www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details.

A brand of **legrand**