

MIGHTY MAC™

TRCD SERIES

PRODUCT FEATURES:

- » Recessed ceiling mount; flange – 24"×24", 24"×48"
- » Continuous heavy gauge hinge for ease of maintenance



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS:

HOUSING: One-piece seam welded type 304 stainless steel construction. See Ordering Information for gauge and finish.

LENS: As specified – maximum inner/outer lens combination thickness .500" – see Ordering Information. Lens sealed to door with silicone caulk and secured with continuous lens retention angles. Kenall recommends a prismatic inner lens and a clear outer lens. Two clear lenses used in combination cannot be provided.

LENS RETENTION: Vertically adjustable continuous "Z" brackets – prime grade material. Secured to door with thru-studs.

DOOR: Type 304 stainless steel construction. See Ordering Information for gauge and finish. Door sealed to housing with closed-cell neoprene gasketing.

HINGE: Continuous heavy gauge stainless steel piano type hinge. Hinge welded to housing and secured to door.

FASTENERS: Torx Head stainless steel fasteners standard. See Options for stainless steel center-pin reject Allen Head (AH) or Phillips Head (PH) fasteners.

FINISH: Brushed stainless steel finish (#4) or white TGIC polyester powder coat – 5-stage pre-treatment; Salt spray test: 1,000 hours; Reflectance: 92%.

LAMPS: Quantity and type as specified – see Ordering Information. Lamps supplied by others.

ELECTRICAL: Electronic ballast <10% THD standard. See Ordering Information for multiple ballasts and optional equipment. Lamps by others.

INSTALLATION: See options for specific mounting hardware required; see Mighty Mac Recessed Flange Mount Technical Data Sheet for more information. For housings without wiring and mounting holes, see Field Drilled Installation Holes (FDIH) Option. Consult factory with questions.

WARRANTY: Limited one (1) year Kenall fluorescent warranty.

LISTINGS: UL and CUL listed for Wet Location. Non IC rated.




ORDERING INFORMATION (Ex: TRCD-2-3/3-2-17-IS-1-120-1/B)

Model	Size	Door/Housing	Lamp Qty	Lamp Type	Ballast Type	Ballast Qty	Voltage	Lens (Inner/Outer)	Options
TRCD		/						/	
Nominal Size			Lamp Quantity			Ballast Quantity			Options
2	24"×24"		2	Two		1	One		AH Allen Head fasteners
4	24"×48"		3	Three		2	Two		CC Cross Channel Mounting Kit
Door/Housing Material			Lamp Type			Voltage			EL Standard Lumen EL Pack
3	14-Ga SS (Painted)		17	F17T8		120	120 Volts		FDIH Field Drilled Installation Holes
4	16-Ga SS (Painted)		31U	F31T8 (3 Lamp Max.)		277	277 Volts		FS Single Fuse & Holder
A	18-Ga SS (Painted)		40B	F40T8		347	347 Volts		PEL High Lumen EL Pack
6*	14-Ga SS (Brushed)		4' Nominal Length			Lens (Inner/Outer)†			PF Plaster Frame Mounting Kit
7*	16-Ga SS (Brushed)		32	F32T8		0	No Lens		PH Phillips Head fasteners
B*	18-Ga SS (Brushed)		44	F48T8HO		1	.125" Prismatic Acrylic		SEL Specified EL Pack
			Ballast Type						SSIN Stainless Steel Interior
			IS Instant Start Electronic <10% THD (T8,T8HO)						YF Yoke Frame Mounting Kit
			RS Rapid Start Electronic <10% THD (CFL,T8,T8HO)						
			SB Specified Ballast						


* Recessed portion of housing not brushed
 † Refer to lens specifications

DIMENSIONAL DATA

CROSS SECTION



MOUNTING HOLES



Recommended Ceiling Cutout: **TRCD2:** 24.00"×25.25" (60.96 cm × 64.14 cm) • **TRCD4:** 24.00"×49.25" (60.96 cm × 125 cm)



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2022 Kenall Mfg. Co.